

The Hiniker logo features the brand name in a bold, red, sans-serif font, enclosed within a black rectangular border with rounded corners.

7 0 0 0 S E R I E S

SNOWPLOWS

H I G H - P E R F O R M A N C E T R I P - E D G E

- *High clearance split trip-edge*
- *Extra strength trussed moldboard frame*
- *Super-Bright quad halogen headlights*
- *Exclusive Hiniker QuickHitch mounting system*



Get Professional Performance With Hiniker Trip-Edge Plows

The horizontal-truss moldboard design provides incredible strength, durability and resistance to bowing. Ten laser-cut support ribs add exceptional vertical strength. The corrosion-proof poly moldboard is dent-resistant with less surface friction for easier plowing and greater efficiency. In addition, impregnated color means long-lasting, good-looking appearance.

HINIKER HIGH-PERFORMANCE TRIP-EDGE



High clearance split trip-edges operate independently of one another, reducing stress and twisting forces on the plow.



Convenient, compact finger-tip control mounts anywhere or can be hand held.




New super-bright quad halogen headlights have up to twice the power of typical sealed beam lamps. Get maximum visibility for added safety, and better, faster plowing operations.

Slick 1/4" HMW poly moldboard surface resists dents, never needs paint.

Externally mounted pump simplifies installation, comes off the truck with the plow.

30-inch tall high curve, high-density polyethylene moldboard is dent-resistant and corrosion-free. Snow flows easily for more efficient plowing. Optional rubber or polyethylene snow deflectors.



Pinch-free pivot point is 9 inches above the surface providing protection from higher obstacles such as curbs and parking barriers.

Long-lasting cast ductile-iron skid shoes.

The high-tensile steel superstructure of the moldboard provides exceptional resistance to bending and bowing, for extra heavy-duty applications. 10 laser-cut steel ribs add exceptional strength.


HINIKER Specifications:

BLADE WIDTH	8'	9'
BLADE HEIGHT	30"	30"
VERTICAL RIBS	10	10
COMPRESSION TRIP SPRINGS	4	4
PLOW WIDTH @ 30° ANGLE	83"	93"
CUTTING EDGE (HIGH CARBON 1084 STEEL)	3/8" x 6"	3/8" x 6"
TRIP HEIGHT	9"	9"
WEIGHT (NET OF TRUCK MOUNTED HARDWARE)	733 lbs.	767 lbs.

Quick Hitch MOUNTING SYSTEM

SPEED, EASE, & SIMPLICITY

The Hiniker Quick Hitch is the fastest plow mounting system available! The self-aligning drive-in mount lets you connect your Hiniker plow in seconds. This eliminates manually lifting, pushing, and pulling the plow into place.



- 1 Drive truck forks into plow receiver
- 2 Pull lever to lock plow to truck & raise stand
- 3 Plug in connections & you're ready to roll!

Reverse the process to disconnect the entire plow assembly just as quickly, leaving it ready for the next snowfall. Because Hiniker makes it so easy to disconnect your plow, you'll save weight and wear on your truck when the plow is not needed.

WE RESERVE THE RIGHT TO AMEND THESE SPECIFICATIONS AT ANY TIME WITHOUT NOTICE. THE ONLY WARRANTY APPLICABLE IS OUR STANDARD WRITTEN WARRANTY. WE MAKE NO OTHER WARRANTY, EXPRESSED OR IMPLIED.



PUT SNOW IN ITS PLACE

HINIKER COMPANY
58766 240 St • P.O. Box 3407
Mankato, MN 56002-3407
Phone (507) 625-6621
Fax (507) 625-5883
www.hiniker.com